

## Secoroc Rotary Products

# Workover Steel Tooth Bits

### 3 7/8" F11

Adding value through performance



- **Cutting Structure**

Straight tooth on gage and inner rows. Hardmetal on heel and inner rows for durability and sustained penetration rates.

Designed for softer formations such as clays, shales, soft sandstones, limestones, siltstone and mud stone.

- **Shirttail Protection**

Regular

- **Application**

Up to 6,000 PSI / 41 MPa

#### Product Specifications:

IADC Code:	1-1-1
Bearing Type:	Ball – Roller – Friction / Without Air Cooled
Circulation Type:	Center Flush Fluid
Cutting Structure:	Steel Tooth
-Inner and Nose Rows	- Straight
- Gage Rows	- Straight
-Gage Bevel Protection	- Hardmetal
Lug/Shirttail Protection:	Regular / Hardmetal
Pin Connection:	2 3/8" API Regular
Metric Bit Diameter:	98 mm
Product Weight:	7.27 lbs / 3.3 kgs
Product Number/Code:	93005004 / 110-0098-11-FO-1R-01

#### Operating Suggestions:

Weight on Bit:	5,800 – 13,600 lbs
Rotary Speed:	60 to 140 RPM

Actual drilling parameters must be determined for specific applications.

**Atlas Copco Secoroc AB**  
Box 521, SE-737 25 Fagersta, Sweden  
Phone: +46 223 461 00  
E-mail: [secoroc@se.atlascopco.com](mailto:secoroc@se.atlascopco.com)  
[www.atlascopco.com](http://www.atlascopco.com)

